

## Features

- Higher Output Voltage and Higher Output Current PIN Diode Driver in Surface Mount Package
- Usable with MSW3200-320 Series High Power Switches.
- Operates from 2 Polarities: +5V and ( - 15V to - 200 V )
- Higher Output Currents ( -50 mA ) for Lower Switch Loss and (+50 mA ) for Higher Isolation.
- Multiple TTL Input Control, 3 Pairs of Complementary Outputs
- RoHS Complaint

## Description

The MPD3T5N200-703 Series of Surface Mount PIN Diode Drivers is designed to provide higher voltage and higher current operation for higher power PIN Diode Switches. In particular, these PIN Diode Drivers are intended to operate with Aeroflex/Metelics MSW3200 Series of Surface Mount, Higher Power SP3T Symmetrical Series-Shunt Switches.

These PIN Diode Drivers operate from + 5V and -15V to - 200V D.C. power supplies to successfully operate the SP2T PIN Diode Switches from 20 – 6,000 MHz for 100 W C.W. or peak power levels. In addition, the Driver can supply current of -50 mA from the -200V supply to provide lower insertion loss and better high signal linearity to the Series PIN Diode. Multiple TTL control is available in the design. The Driver provides 3 pairs of complementary outputs that drive the bias ports in the SP3T PIN diode Switch. Propagation Delay (50 % TTL-10% RF Voltage) is on the order of 1 uS and can be improved with external RC, current spiking network.

The PIN Diode Driver is designed in a 1.3 " square x 0.33 " H ( 33 mm sq x 8.4 mm H ) surface mount package. The devices are available in tube and tape-reel packaging for high volume pick and place automated assembly and are RoHS compliant.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## Applications

The MPD3T5N200-703 Driver Series is designed to be used in higher voltage and higher current PIN Diode switch applications, operating from 20 MHz to 6 GHz, requiring high volume, surface mount, solder re-flow manufacturing. These products are durable, reliable, and capable of meeting all military, commercial, and industrial environments.

## Environmental Capabilities

The MPD3T5N200-703 Driver Series is capable of meeting the environmental requirements of MIL-STD-202 and MIL-STD-750.

## ESD and Moisture Sensitivity Level Rating

Semiconductor Devices are susceptible to ESD conditions and environments. The ESD rating for this device is Class 1A, HBM. The moisture sensitivity level rating for this device is MSL 1.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

# MPD3T5N200-703 Electrical Specifications @ Tambient = +25°C ( Unless Otherwise Defined )

| Parameter                                              | Symbol      | Units   | Test Conditions                                                                              | Minimum Value | Typical Value | Maximum Value |
|--------------------------------------------------------|-------------|---------|----------------------------------------------------------------------------------------------|---------------|---------------|---------------|
| Operating Frequency<br>( PRF )                         | F           | kHz     | +VCC = +5V, -VEE = -15V to -200V                                                             | D.C.          | 0 – 100       | 500           |
| Input Voltage 1                                        | +VCC        | V       | +VCC = +5V, -VEE = -15V to -200V                                                             | + 4.5         | +5.0          | + 5.5         |
| Input Voltage 2                                        | -Vee        | V       | +VCC = +5V, -VEE = -15V to -200V                                                             | -15           | -50           | -200          |
| +VCC Input Quiescent Current                           | +IQ1        | mA      | +VCC = +5V, -VEE = -15V to -200V<br>Vout1 = V out2 = $\infty\Omega$                          | 10            | 20            | 30            |
| -VEE Input Quiescent Current                           | +IQ2        | mA      | +VCC = +5V, -VEE = -15V to -200V<br>Vout1 = V out2 = $\infty\Omega$                          | -15           | -25           | -40           |
| TTL Input Voltage CTL1                                 | VTTL        | V       | Logic 0 @ 20uA sink current<br>Logic 1 @ 0.5mA source current                                | 0.0<br>2.0    |               | 0.8<br>5.0    |
| Low Level Output Voltage @ V1a, V1b V2a, V2b V3a, V3b  | VoutL       | V       | +VCC = +5V, -VEE = -15V to -200V<br>Current from +VCC = + 50 mA                              | +VCC – 1.0V   | +VCC – 0.5V   | +VCC – 0.1V   |
| High Level Output Voltage @ V1a, V1b V2a, V2b V3a, V3b | VoutH       | V       | +VCC = +5V, -VEE = -15V to -200V<br>Current from –VEE = - 50 mA                              | -VEE + 0.1V   | -VEE + 0.5V   | -VEE + 1.0V   |
| Switching Speed<br>( Note 1 )                          | Ton<br>Toff | $\mu$ S | +VCC = +5V, -VEE = -15V to -200V<br>F = 10 kHz ( 50 % TTL – 10 % or 90 % RF Output Voltage ) |               | 1.5           | 2.0           |

## Notes:


1. Switching Speed is measured using the Aeroflex/Metelics MSW3200-320 Symmetrical SP3T @ 2.5 GHz @ +VCC = +5V & -VEE = -50 V in the commutating switching mode.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)


# MPD3T5N200-703 PIN Diode Driver Schematic



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)


## MPD3T5N200-703 PIN Diode Driver with an external RC Spiking Network.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## MPD3T5N200-703 PIN Diode Driver and Series-Shunt SP3T as D.C. Load



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## Notes for MPD3T5N200-703 with Series-Shunt SP3T:

1. Low Output Voltage Current,  $I_{shunt}$ , ( from  $+V_{CC} = +5V$  ) to Forward Bias the ON SHUNT PIN Diode ( Isolation State ) is determined by the bias resistor,  $R_{shunt}$ , according to Ohm's Law :
2.  $R_{shunt} = ( +5V - \Delta V_{diode} - V_{CESsat} ) / ( I_{shunt} ) = ( +3.6V ) / ( I_{shunt} )$ .  $I_{shunt}$  range = + 5 to + 50 mA.
3. High Output Voltage Current,  $-I_{series}$ , ( from  $-V_{EE}$  ) to Forward Bias the ON SERIES PIN Diode ( Insertion Loss State ) is determined by the bias resistor,  $R_{series}$ , according to Ohm's Law :
4.  $R_{series} = ( -V_{EE} + 2\Delta V_{diode} + V_{CESsat} ) / ( I_{series} ) = ( -V_{EE} + 2.3V ) / ( I_{series} )$ .  $-I_{series}$  range = -5 to -50 mA. As Example, using  $-V_{EE} = -200V$  and requiring  $-I_{series} =$  for -50 mA,  $R_{series} = -197.7V/0.05A = 3.95K\Omega$ . Power Dissipation =  $I^2 R = ( 5E-2 )^2 ( 3.95 E+3 ) = 9.9 W$ .
5. Switching Speed ( 50 % TTL – 10/90 % RF Voltage ) is a Function of the PIN Diode Driver Performance. A RC “ Current Spiking Network” is used on the Driver outputs ( V1a & V1b ) to provide a  $I_c = C dV/dt$  transient current to move Stored charge through the PIN Diode, typical values are:
6.  $R_{shunt} = 68 - 680 \Omega$  and  $C1 = 470 - 1,000 pF$ .
7. For Hot Switching Applications, PIN Diode Driver must Transition from Forward Bias to Reverse Bias and Reverse Bias to Forward Bias within 500 ns ( 10 % - 90 % Output Voltage ) with a parallel RC spiking network at the Driver Output ( V1a & V1b ) per Note 3.

## MPD3T5N200-703 PIN Diode Driver and MSW3200-320 Symmetrical SP3T Truth Table using $+V_{CC} = +5 V @ + 20 mA$ and $-V_{EE} = -50 V @ -50 mA$ .

| RF State                                           | J1 Bias        | J2Bias         | J3Bias         | TTL Logic                        |
|----------------------------------------------------|----------------|----------------|----------------|----------------------------------|
| J1-J0 Low Loss & J2-J0 Isolation & J3-J0 Isolation | -180V @ -50 mA | + 1 V @ +25 mA | + 1 V @ +25 mA | CTL1 = 1<br>CTL2 = 0<br>CTL3 = 0 |
| J2-J0 Low Loss & J1-J0 Isolation & J3-J0 Isolation | + 1 V @ +25 mA | -180V @ -50 mA | + 1 V @ +25 mA | CTL1 = 0<br>CTL2 = 1<br>CTL3 = 0 |
| J3-J0 Low Loss & J1-J0 Isolation & J2-J0 Isolation | + 1 V @ +25 mA | + 1 V @ +25 mA | -180V @ -50 mA | CTL1 = 0<br>CTL2 = 0<br>CTL3 = 1 |



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## MPD3T5N200-703 PIN Diode Driver Input Output ( I/O ) Table

| I/O Port       | Description                        |
|----------------|------------------------------------|
| J1 ( PIN 1 )   | +VCC & -VEE RTN                    |
| J2 ( PIN 2 )   | +VCC & -VEE RTN                    |
| J3 ( PIN 3 )   | +VCC & -VEE RTN                    |
| J4 ( PIN 4 )   | V1a ( Voltage/Current Output #1a ) |
| J5 ( PIN 5 )   | V1a ( Voltage/Current Output #1b ) |
| J6 ( PIN 6 )   | V2a ( Voltage/Current Output #2a ) |
| J7 ( PIN 7 )   | V2b ( Voltage/Current Output #2b ) |
| J8 ( PIN 8 )   | V3a ( Voltage/Current Output #3a ) |
| J9 ( PIN 9 )   | V3b ( Voltage/Current Output #3b ) |
| J10 ( PIN 10 ) | -VEE                               |
| J11 ( PIN 11 ) | +VCC & -VEE RTN                    |
| J12 ( PIN 12 ) | +VCC & -VEE RTN                    |
| J13 ( PIN 13 ) | +VCC                               |
| J14 ( PIN 14 ) | TTL Input Control ( CTL3 )         |
| J15 ( PIN 15 ) | TTL Input Control ( CTL2 )         |
| J16 ( PIN 16 ) | TTL Input Control ( CTL1 )         |



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## Absolute Maximum Ratings Specifications @ Tambient = +25°C ( Unless Otherwise Defined )

| Parameter                  | Absolute Maximum Value            |
|----------------------------|-----------------------------------|
| INPUT Voltage 1 ( +VCC )   | -0.1 V to + 5.5 V                 |
| INPUT Voltage 2 ( -VEE )   | +0.1 V to – 210 V                 |
| TTL INPUT Voltage ( CTL1 ) | -0.5 V to + 5.5 V                 |
| +VCC Source Current        | +60 mA                            |
| -VEE Source Current        | -60 mA                            |
| Operating Temperature      | - 65 °C to + 125 °C               |
| Storage Temperature        | - 65 °C to + 150 °C               |
| Junction Temperature       | + 175 °C                          |
| Assembly Temperature       | + 260 °C for 10 Seconds           |
| Total Dissipated D.C Power | 6.0W @ +85 Deg C Case Temperature |

## Assembly Instructions

The MPD3T5N200-703 PIN Diode Drivers are capable of being placed onto circuit boards with pick and place manufacturing equipment from tube or tape-reel dispensing. The devices are attached to the circuit board using conventional solder re-flow or wave soldering procedures with RoHS type or Sn 63 / Pb 37 type solders per Table I and Graph I Time-Temperature recommended profile.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

**Table 1: Time-Temperature Profile for Sn 60/Pb40 or RoHS Type Solders**


| Profile Feature                                                                                                                                                                                        | Sn-Pb Eutectic Assembly          | Pb-Free Assembly                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|----------------------------------|
| Average ramp-up rate<br>( $T_L$ to $T_p$ )                                                                                                                                                             | 3°C/second max.                  | 3°C/second max.                  |
| Preheat <ul style="list-style-type: none"> <li>– Temperature Min (<math>T_{SMIN}</math>)</li> <li>– Temperature Max (<math>T_{SMAX}</math>)</li> <li>– Time (min to max) (<math>t_s</math>)</li> </ul> | 100°C<br>150°C<br>60-120 seconds | 150°C<br>200°C<br>60-180 seconds |
| $T_{SMAX}$ to $T_L$ <ul style="list-style-type: none"> <li>– Ramp-up Rate</li> </ul>                                                                                                                   |                                  | 3°C/second max                   |
| Time maintained above: <ul style="list-style-type: none"> <li>– Temperature (<math>T_L</math>)</li> <li>– Time (<math>t_l</math>)</li> </ul>                                                           | 183°C<br>60-150 seconds          | 217°C<br>60-150 seconds          |
| Peak Temperature ( $T_p$ )                                                                                                                                                                             | 225 +0/-5°C                      | 245 +0/-5°C                      |
| Time within 5°C of actual<br>Peak Temperature ( $t_p$ )                                                                                                                                                | 10-30 seconds                    | 20-40 seconds                    |
| Ramp-down Rate                                                                                                                                                                                         | 6°C/second max.                  | 6°C/second max.                  |
| Time 25°C to Peak<br>Temperature                                                                                                                                                                       | 6 minutes max.                   | 8 minutes max.                   |



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)


## Graph1: Solder Re-Flow Time-Temperature Function



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## Outline Drawing Case Style 703 (CS 703)



Backside area of PIN Diode Driver has a keep out area that should not contain any conductors or return (Ground) lines.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)

## Part Number Ordering Information:

| Part Number      | Packaging                                         |
|------------------|---------------------------------------------------|
| MPD3T5N200-703-R | Tape-Reel Packaging<br>(Quantities of 250 or 500) |
| MPD3T5N200-703-W | Waffle Packaging                                  |
| MPD3T5N200-703-E | Evaluation Board                                  |

East Coast Operations  
Aeroflex / Metelics  
54 Grenier Field Road  
Londonderry , NH 03053 [USA]  
Phone: (603) 641-3800  
Toll Free: (888) 641-SEMI (7364)  
Fax: (603) 641-3500

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of a product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties. Copyright 2008 Aeroflex / Metelics. All rights reserved.



ISO 9001:2008

TEL: 603-641-3800 • [metelics-sales@aeroflex.com](mailto:metelics-sales@aeroflex.com) • [www.aeroflex.com/metelics](http://www.aeroflex.com/metelics)