



	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Production</u> <u>Test</u>	<u>First Article</u> <u>Test</u>
Frequency Range	4130		4730	MHz	1	☐	☐
Tuning Voltage	0.2		7.0	V	1	☐	☐
Modulation Sensitivity		150		MHz/V	3	☐	☐
Operates with Vtune = 0V					3	☐	☐
Output Power	-3	0	3	dBm	1	☐	☐
Phase Noise @							
1 KHz Offset		-53	-49	dBc/Hz	2	☐	☐
10 KHz Offset		-82	-78	dBc/Hz	3	☐	☐
100 KHz Offset		-108	-104	dBc/Hz	2	☐	☐
1 MHz Offset		-132	-128	dBc/Hz	2	☐	☐
10 MHz Offset		-153	-149	dBc/Hz	2	☐	☐
Pushing		5	8	MHz/V	3		☐
Pulling (12 dB R.L.)		3	5	MHz	3		☐
Modulation Bandwidth		5		MHz	4		
Tuning Port Capacitance		20		pF	2		
Harmonics		-15	-10	dBc	3		☐
Vcc		5		V	5		☐
Icc		10		mA	5	☐	☐
Operating Temperature	-40		+85	C	3		☐
Package		SMUA					
LxW		0.500		inch sq.	5	☐	☐
Height		0.220		inch	5	☐	☐

Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection