



VCO R007008SMUA(D14)5-FF

rev_0

initial rev

						Production	First Article
	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Test</u>	<u>Test</u>
Frequency Range	68		80	MHz	1	☐	☐
Tuning Voltage	1.5		11	V	1	☐	☐
Modulation Sensitivity		2		MHz/V	1	☐	☐
Operates with Vtune = 0V					1	☐	☐
Output Power	7	9	11	dBm	1	☐	☐
Phase Noise @							
1 KHz Offset		-108	-103	dBc/Hz	1	☐	☐
10 KHz Offset		-133	-128	dBc/Hz	1	☐	☐
100 KHz Offset		-153	-148	dBc/Hz	1	☐	☐
1000 KHz Offset		-164	-155	dBc/Hz	1	☐	☐
Pushing		0.05	0.1	MHz/V	3	☐	☐
Pulling (12dB RL, any phase)		0.1	0.2	MHz _{p-p}	3	☐	☐
Tuning Port Capacitance		1000		pF	2	☐	☐
2nd Harmonic		-20	-15	dBc	3	☐	☐
Vcc		5.0		V	1		
Icc		16		mA	1	☐	☐
Operating Temperature	-40		+85	C	3	☐	☐
Package		SMUA(D14)			6,8	☐	☐
LxW		0.500		inch sq.	5	☐	☐
Height		0.220		inch	5	☐	☐

Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection
6. RoHS compliant
7. Parylene Conformal Coating
8. Foam Filled
9. Conformal Coating and Foam Fill
10. Design goal subject to change