



	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	Production <u>Test</u>	First Article <u>Test</u>
Frequency Range	840		950	MHz	1	..	..
Tuning Voltage	0		12	V	1	..	..
Modulation Sensitivity		9.5		MHz/V	1,10	..	..
Operates with Vtune = 0V					1	..	..
Output Power	3	5	7	dBm	1	..	..
Phase Noise @							
1 KHz Offset		-92	-87	dBc/Hz	1	..	..
10 KHz Offset		-119	-114	dBc/Hz	1	..	..
100 KHz Offset		-140	-135	dBc/Hz	1	..	..
1 MHz Offset		-160	-155	dBc/Hz	1	..	..
10 MHz Offset		-164	-155	dBc/Hz	1	..	..
Pushing		0.3		MHz/V	3	..	..
Pulling (12dB RL, any phase)		0.4		MHz _{p-p}	3	..	..
Modulation Bandwidth		1		MHz	4	..	..
Tuning Port Capacitance		47		pF	2	..	..
Harmonics		-15	-10	dBc	3	..	..
Vcc	5.0	5.5	6.0	V		..	..
Icc		26		mA	1	..	..
Operating Temperature	-40		+85	C	3	..	..
Package		SMUA			6	..	..
LxW		0.500		inch sq.	5	..	..
Height		0.220		inch	5	..	..

Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection
6. RoHS compliant
7. Parylene Conformal Coating
8. Foam Filled
9. Conformal Coating and Foam Fill
10. Design goal subject to change