



R1415SMUA5_180

rev_0

initial rev

	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Production Test</u>	<u>First Article Test</u>
Frequency Range	1400		1500	MHz	1	☐	☐
Tuning Voltage	0.5		4.5	V	1	☐	☐
Modulation Sensitivity		36		MHz/V	1	☐	☐
Operates with Vtune = 0V					1	☐	☐
Output Power	-2.5	0	2.5	dBm	1	☐	☐
Phase Noise @							
1 KHz Offset		-83	-78	dBc/Hz	1	☐	☐
10 KHz Offset		-109	-104	dBc/Hz	1	☐	☐
100 KHz Offset		-129	-124	dBc/Hz	1	☐	☐
1 MHz Offset		-149	-144	dBc/Hz	1	☐	☐
Pushing		1	2	MHz/V	3	☐	☐
Pulling (12dB RL, any phase)		1	2	MHz _{p-p}	3	☐	☐
Modulation Bandwidth		1000		MHz	4	☐	☐
Tuning Port Capacitance		47		pF	2	☐	☐
Harmonics		-15	-10	dBc	3	☐	☐
Vcc		5.0		V			
Icc		25		mA	1	☐	☐
Operating Temperature	-40		+85	C	3	☐	☐
Package		SMUA			6	☐	☐
LxW		0.500		inch sq.	5	☐	☐
Height		0.180		inch	5	☐	☐

Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection
6. RoHS compliant
7. Parylene Conformal Coating
8. Foam Filled
9. Conformal Coating and Foam Fill
10. Design goal subject to change