





	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Production Test</u>	<u>First Article Test</u>
Frequency Range	2014		2081	MHz	1	..	..
Tuning Voltage	0.5		4.5	V	1	..	..
Modulation Sensitivity		22		MHz/V	1	..	..
Operates with Vtune = 0V					1	..	..
Output Power	5	7	9	dBm	1	..	..
Phase Noise @							
1 KHz Offset		-88	-83	dBc/Hz	1	..	..
10 KHz Offset		-115	-110	dBc/Hz	1	..	..
100 KHz Offset		-135	-130	dBc/Hz	1	..	..
1 MHz Offset		-155	-150	dBc/Hz	1	..	..
10 MHz Offset		-165	-160	dBc/Hz	1	..	..
Pushing		0.3	0.6	MHz/V	3	..	..
Pulling (12dB RL, any phase)		0.5	1	MHz _{p-p}	3	..	..
Modulation Bandwidth		1		MHz	4	..	..
Tuning Port Capacitance		47		pF	2	..	..
Harmonics		-17	-10	dBc	3	..	..
Vcc		5.0		V		..	..
Icc		27		mA	1	..	..
Operating Temperature	-40		+85	C	3	..	..
Package		SMUA			6	..	..
LxW		0.500		inch sq.	5	..	..
Height		0.220		inch	5	..	..

Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection
6. RoHS Compliant
7. Design goal subject to change




SMUA PACKAGE

SHEET 1 OF 2



CONTACT DIMENSIONS



Scale: 16:1



DRAWN NAME
Stefan Babulal

DATE
2/20/2017

COMMENTS:
All dimensions are in inches.
Tolerances ± 0.005 unless otherwise noted

TITLE:

SMUA PACKAGE

SIZE	DWG. NO.	REV
A	1	


SCALE: 6:1	unit: inch	SHEET 2 OF 2
------------	------------	--------------




TOP VIEW



BOTTOM VIEW



SIDE VIEW



ISOMETRIC VIEW