




7901-031-K003




NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: GASKET - SILICONE RUBBER PER ZZ-R-765
CONTACT & LOCK RING - BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04.
FERRULE - BRASS PER ASTM B16.
INSULATOR - OXIDE-NORYL PER MIL-P-48129
ALL METAL PARTS - CORROSION RESISTANT STEEL PER ASTM A582, ALLOY UNS S30300, TYPE 1
3. FINISHES: COUPLING NUT - PASSIVATE PER SAE AMS-A2700
CONTACT & BODY - GOLD PLATE PER ASTM B488, TYPE 2, CODE C, CLASS 1.27 OVER
NICKEL PER AMS-Q--N-290, CLASS 1, .00005" MIN.

4. ELECTRICAL REQUIREMENTS

- FREQUENCY RANGE: DC-40.0 GHz
- INSERTION LOSS: .03 FGHz dB MAX
- VSWR: 1.15 MAX: DC TO 18 GHz
1.3 MAX: 18 TO 40 GHz
- NOMINAL IMPEDANCE: 50 OHM



RECOMMENDED CABLE PREPARATION

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: SMK (2.92MM) DIRECT SOLDER PLUG
FOR .141 DIA. SEMI-RIGID CABLE

Drawn by STM	Scale 4/1	Ckd. by MR	Engr Appd MR	FILE NAME: 7901031K003-000T
-----------------	--------------	---------------	-----------------	--------------------------------

CODE IDENT.-00795

7901-031-K003

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.008, 2 PLACES = ±.02, ANGLES = ±1/2°, SURFACE FINISH = 63

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.