



VCO Product Specification

Model: RFVC6405 **Rev:** A **Date:** 4/24/2015
Customer: RF MICRO DEVICES
Operating Temperature Range: (-40 ° to 85 ° C)

RoHS Compliant

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	2000		4000	MHz	X	
Tuning Voltage -	0		16	Vdc	X	
Tuning Sensitivity -		150		MHz/V	X	
Output Power:						
	-3	0	3	dBm	X	
	-4			dBm		@Vt=0
Output Phase Noise:						
1 kHz		-60	-55	dBc/Hz		
10 kHz		-90	-85	dBc/Hz	X	
100 kHz		-112	-105	dBc/Hz		
1000 kHz		-132	-125	dBc/Hz		
Power Supply -		5		Volts	X	
Supply Current -		25	30	mA	X	
Harmonic Suppression:						
2nd Harmonic		-15		dBc	X	
Frequency Pulling -		4		MHz p-p		@12dBr, all phases
Output Impedance -		50		Ω		
Frequency Pushing (MHz/V) -		4		MHz/V		

Package Information

Package Type:	R16 (0.5 x 0.5 x 0.18 inches)	Drawing Number:	UP-R16
---------------	-------------------------------	-----------------	--------

Comments

X Indicates parameter to be tested 100% in production

Device w/o Buffer Amp.

Frequency Drift with Temperature: @ -40 degree C, 22.0 MHz Typical.

Frequency Drift with Temperature: @ +85 degrees C, 18.0 MHz Typical.

RoHS status based on EU Directive 2011/65/EU (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("Qorvo") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of Qorvo. Qorvo reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.

Page 1 of 1