




Coax HEX Dies for RFA-4005-20 Crimper

Buy separately or with tool

For your convenience we offer our commercial grade crimp dies conveniently packaged with the RFA-4005-20 crimp handle in a cardboard box.



- Ratchet action with auto release with completed crimping
- High-carbon, heat-treated stamped steel
- Smooth, rapid die closure
- Disengagement lever for quick release
- Simple adjustment for die size and pressure requirements

Specific Die	Part Number for Die with Crimp Tool in Cardboard Box
RFA-4005-01	RFA-4005-400
RFA-4005-02	RFA-4005-300
RFA-4005-04	RFA-4005-304
RFA-4005-05	RFA-4005-305
RFA-4005-06	RFA-4005-306
RFA-4005-07	RFA-4005-307
RFA-4005-08	RFA-4005-308
RFA-4005-09	RFA-4005-309
RFA-4005-10	RFA-4005-310
RFA-4005-14	RFA-4005-314



RFA-4005-01

RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, Proflex and various video cables, cavity dimensions: .052", .068", .100", .213" and .255".



RFA-4005-07

.213", .178", .068", .042", for RG-58/U, RG-174/U, RG-316/U Coax Connectors (RFI Cable Groups B and C)



RFA-4005-02

RG-8/U, RG-213/U, RG-214/U, and Belden 9913 cables, cavity dimensions: .100", .128" & .429". The .128" cavity crimps the center pin on Belden 9913 cable.



RFA-4005-08

.324", .255", .068", .042", for RG-59/U and Belden 8281 Coax Cable (RFI Cable Groups D and G)



RFA-4005-04

.239", .068", .319", for RG-58/U, RG-59/U, RG-62/U and Cambridge connectors series CP-88 & CP-89



RFA-4005-09

.178", .130", .068", for RG-174/U, RG-188/U, RG-316/U and Mini 59/U Coax Connectors (RFI Cable Group B)



RFA-4005-05

.155", .184", .215"



RFA-4005-10

.080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI Cable Group E)



RFA-4005-06

.255", .324", .360" for RG-59/U, RG-6/U, and F-Type (CATV) Coax Connectors



RFA-4005-14

Belden 9913, LMR®-400, WBC-400 (RFI Cable Group I); .429", .118" hex cavities

TOOLS & Acc.