

Overview

Southwest Antennas Part # 1001-134 is a half wave dipole omni antenna with a frequency range of 1.35 to 1.40 GHz and 2.15 dBi of peak gain. This product features an integrated RF bandpass filter to help eliminate interference from other co-located radios operating outside of the antenna's 1.35 - 1.40 GHz operational frequency range, providing increased performance for attached radios.

1001-134 features an integrated 3" RF Gooseneck with black chrome Reverse Polarity TNC(m) RF connector, which contributes to the improvement of RF link margin and overall antenna performance. Our proprietary antenna design and manufacturing process ensures optimum antenna RF performance.

The Reverse Polarity TNC(m) RF connector can be easily secured or removed from equipment in the field by a single gloved hand, no tools required.

Antennas with integrated RF Goosenecks are ideal for handheld video receivers, portable radio systems, or any other mobile communication platform. The RF Gooseneck can be threaded through MOLLE gear or other tactical vest hardware for added security while moving.

A rugged flat black fiberglass radome provides protection from damage and gives the antenna a low visibility finish. The integrated RF Gooseneck allows the antenna to bend and deflect away from impacts during indoor or outdoor operations.

Features


- Broad Band Coverage
- Half Wave Dipole
- 1.35 - 1.40 GHz
- 2.15 dBi Omni Radiation Pattern
- Internal 3-Pole RF Bandpass Filter
- 8W Power Handling
- Integrated 3-Inch RF Coaxial Gooseneck
- Rugged Flat Black Fiberglass Radome
- Black Chrome Reverse Polarity TNC(m) RF Connector



Product Specifications

Parameter	Value	Units	Tolerance
Antenna Pattern	Omni		
Frequency Band	L		
Impedance	50		
Minimum Frequency	1.35 / 1,350	GHz / MHz	
Maximum Frequency	1.4 / 1,400	GHz / MHz	
Frequency Bandwidth	0.05 / 50	GHz / MHz	
Maximum VSWR	2:1	Ratio	
Maximum Gain	2.15	dBi	
Polarization	Vertical		
Color	Flat Black		
Maximum RF Input Power	8	Watts	
Horizontal AZ Beamwidth	360	Degrees	
Vertical EL Beamwidth	77	Degrees	
Radome Material	Fiberglass G10		
Spring Or Gooseneck	Gooseneck		
Spring	No		
Gooseneck	Yes		
Gooseneck Length	3 / 76	inches / mm	±0.09"
Gooseneck Diameter	0.35 / 8.89	inches / mm	+ .010" / - .005"
Ground Plane Required	No		
RF Connector Type	RP-TNC(m)		
RF Connector Finish	Black Chrome		

Parameter	Value	Units	Tolerance
Product Height	9.75 / 247.65	inches / mm	±0.15"
Product Diameter	0.562 / 14.275	inches / mm	+0.02" / -.000"
Product Weight	2.00 / 56.70	oz / g	
Filter Specifications			
Parameter	Value	Units	Tolerance
Filter Type	3mm, 3-Pole Bandpass Filter		
Filter Frequency Band	L Band		
Filter Impedance	50	Ohms	
Filter Minimum Frequency	1350	MHz	
Filter Maximum Frequency	1400	MHz	
Return Loss	15	dB	Over 100% of BW
Rejection 1	-50	dBc	Min @ 960 MHz
Rejection 2	-40	dBc	Min @ 1,850 MHz
Filter Power CW	8	Watts	
Filter Power Peak	10	Watts	
Filter Operating Temp	-40 to +85	C	



Elevation Pattern

Referenced to +5dBi





Image Filter



Engineering Drawing

All dimensions are in inches